



Aluminium Impact Wrench

Twin Hammer



24212B

- Handle air exhaust
- High nut breaking torque
- Durable and powerful clutch system



1/2" Dr. 24242 3/8" Dr. 23242

- The working width is only 145 mm (5.7") and it is suitable for the area hard to reach.
- 3-Speed forward power setting and 3-Speed in reverse
- Max. power delivery up to 542 Nm (400 ft-lb)



3/4" 26208 6" Anvil 26208L 1" 28208 6" Anvil 28208L

- Most powerful and compact, deliver best Power-to-Size ratio in this class
- 3-position power management in forward and 3-position in reverse
- Handle exhaust

Item No.	Speed RPM	Square Drive	Max. Torque Nm/ft-lb	Length mm/inch	Weight kg/lb	Air Consumption LPM / CFM	Air Inlet inch	Vibration m/s²	Noise Level LpA / LwA	Working Pressure Bar / PSI
24212B	8,000	1/2"	745 (550)	185 (7.3)	2.6 (5.7)	113 (4.0)	1/4	8.19	97.1 / 108.1 DB	6.2 (90)
24242	12,000	1/2"	542 (400)	145 (5.7)	1.6 (3.5)	100 (3.5)	1/4	8.58	89.8 / 100.8 DB	6.2 (90)
23242	12,000	3/8"	542 (400)	145 (5.7)	1.6 (3.5)	100 (3.5)	1/4	8.58	89.8 / 100.8 DB	6.2 (90)
26208	7,500	3/4"	1,898 (1,400)	210 (8.3)	3.9 (8.6)	119 (4.2)	3/8	8.43	95.9 / 106.9 DB	6.2 (90)
26208L	7,500	3/4"	1,627 (1,200)	358 (14.1)	4.7 (10.3)	119 (4.2)	3/8	8.43	95.9 / 106.9 DB	6.2 (90)
28208	7,500	1"	2,034 (1,500)	213 (8.4)	4.2 (9.2)	119 (4.2)	3/8	8.75	93.4 / 104.4 DB	6.2 (90)
28208L	7,500	1"	1,761 (1,300)	366 (14.4)	5.0 (11.0)	119 (4.2)	3/8	8.75	93.4 / 104.4 DB	6.2 (90)



24209

- Handle air exhaust
- Most powerful 1/2" impact wrench up to 1,085 Nm (880 ft-lb)
- 3-speed forward power setting and also 3-speed power setting in reverse



26209

- **Light weight and high torque output**
- Handle air exhaust
- 3-speed forward power setting and also 3-speed power setting in reverse



28209 6" Anvil 28209L

- **Light weight and powerful**
- Handle air exhaust
- Comes with side handle

Item No.	Speed RPM	Square Drive	Max. Torque Nm/ft-lb	Length mm/inch	Weight kg/lb	Air Consumption LPM / CFM	Air Inlet inch	Vibration m/s²	Noise Level LpA / LwA	Working Pressure Bar / PSI
24209	7,500	1/2"	1,085 (880)	178 (7.0)	2.6 (5.7)	187 (6.6)	1/4	6.24	97.4 / 108.4 DB	6.2 (90)
26209	7,500	3/4"	1,490 (1,100)	178 (7.0)	2.7 (5.9)	187 (6.6)	1/4	6.08	97.4 / 108.4 DB	6.2 (90)
28209	4,500	1"	2,440 (1,800)	240 (9.4)	5.5 (12.1)	204 (7.2)	3/8	6.10	97.0 / 108.0 DB	6.2 (90)
28209L	4,500	1"	2,440 (1,800)	392 (15.4)	6.3 (13.9)	204 (7.2)	3/8	6.10	97.0 / 108.0 DB	6.2 (90)