



Hammer, Flux Chipper, Needle Scaler

- *Pneutrend riveting hammer for riveting, king pin removal, bushing driving and boat shearing*



42201 Shank 10 mm (0.4")



42202 (2X), 42203 (3X)
42204 (4X) Shank 10 mm (0.4")



42305 (5X), 42307 (7X)
42309 (9X) Shank 12.7 mm (0.5")

- *For surface preparation work involving the cleaning or removal of paint, rust or weed slag*



43201



43204



44204 Needle 3 mm x 19 pcs



44302 Needle 3 mm x 28 pcs



44207 Needle 3 mm x 19 pcs



44301 Needle 4 mm x 35 pcs

Item No.	Speed BPM 	Stroke mm/inch 	Piston D. mm/inch 	Length mm/inch 	Weight kg/lb 	Air Consumption LPM / CFM 	Air Inlet inch 	Vibration m/s² 	Noise Level LpA / LwA 	Working Pressure Bar / PSI
42201	2,160	73 (2.9)	12.7 (0.5)	208 (8.2)	1.3 (2.9)	50 (1.7)	1/4	23.1	101 / 112 DB	6.2 (90)
42202	2,600	57 (2.3)	12.7 (0.5)	154 (6.1)	1.2 (2.6)	50 (1.7)	1/4	23.1	101 / 112 DB	6.2 (90)
42203	2,200	73 (2.9)	12.7 (0.5)	185 (7.3)	1.3 (2.9)	50 (1.7)	1/4	25.9	101 / 112 DB	6.2 (90)
42204	1,800	78 (3.1)	12.7 (0.5)	211 (8.3)	1.4 (3.1)	50 (1.7)	1/4	28.8	97 / 108 DB	6.2 (90)
42305	1,600	68 (2.7)	19.0 (0.8)	227 (9.0)	1.7 (3.7)	63 (2.2)	1/4	12.5	95 / 106 DB	6.2 (90)
42307	1,140	98.4 (3.9)	19.0 (0.8)	252 (9.9)	2.2 (4.8)	63 (2.2)	1/4	9.4	100 / 111 DB	6.2 (90)
42309	900	148 (5.8)	19.0 (0.8)	300 (11.8)	2.7 (5.9)	63 (2.2)	1/4	19.5	100 / 111 DB	6.2 (90)
43201	4,800	32 (1.2)	22.0 (0.9)	235 (9.3)	1.1 (2.4)	85 (3.0)	1/4	26.59	92 / 103 DB	6.2 (90)
43204	5,000	33 (1.3)	25.0 (1.0)	420 (16.5)	1.8 (4.0)	198 (7.0)	1/4	31.01	98 / 109 DB	6.2 (90)
44204	4,600	38 (1.5)	25.0 (1.0)	460 (18.1)	2.8 (6.2)	232 (8.2)	1/4	7.74	99 / 110 DB	6.2 (90)
44302	3,500	28 (1.1)	28.0 (1.1)	350 (13.8)	3.6 (7.9)	210 (7.4)	3/8	8.06	99 / 110 DB	6.2 (90)
44207	3,700	33 (1.3)	23.5 (0.9)	330 (13.0)	2.7 (5.9)	85 (3.0)	1/4	18.1	98 / 109 DB	6.2 (90)
44301	2,500	52 (2.0)	33.0 (1.3)	460 (18.1)	6.0 (13.2)	210 (7.4)	1/4	28.56	100 / 111 DB	6.2 (90)