



ECD Impact Wrench

- **Tri-Lobe Clutch** : Suitable for industrial maintenance and production
- **Smooth & Gradual build-up to "peak" torque** : It gives you full control and comfort even at high torque application.
- **Less energy waste and lower air consumption** when compared with other impact mechanisms
- **Lightweight, Durable, Powerful and Low Vibration !**
- **3 settings in forward and full power in reverse**



Advantages of Tri-Lobe Clutch

- High Torque
- Low Vibration
- Long Durability



1/2"
24739
Tri-Lobe Clutch



1/2" 3/4"
24239 26239
Twin Hammer Clutch



Easy Change Direction in Forward and Reverse

Short Profile 114 mm



1.1 kgs Only !

Mini 3/8" Mini 1/2"
23238 24238
Twin Hammer Clutch



- 1 x 1/2" Stubby Impact Wrench (24238)
3 x Deep Sockets (75 mm) : 17, 19 & 21 mm
8 x **Short** Sockets (28 mm) : 14, 15, 16, 17, 19, 21, 22 & 24 mm
1 x 3" Extension Bar
1 x Oiler
1 x Blow Mould Case



Ideal for very restricted areas !

Item No.	Speed RPM	Square Drive	Max. Torque Nm/ft-lb	Length mm/inch	Weight kg/lb	Air Consumption LPM / CFM	Air Inlet inch	Vibration m/s²	Noise Level LpA / LwA	Working Pressure Bar / PSI
23238	10,000	3/8"	434 (320)	114 (4.5)	1.1 (2.4)	136 (4.8)	1/4	7.48	84.6 / 95.6 DB	6.2 (90)
24238	10,000	1/2"	816 (600)	114 (4.5)	1.1 (2.4)	136 (4.8)	1/4	7.48	84.6 / 95.6 DB	6.2 (90)
24239	7,500	1/2"	1,335 (1,000)	165 (6.5)	1.8 (4.0)	139 (4.9)	1/4	9.11	95.7 / 106.7 DB	6.2 (90)
24739	7,500	1/2"	1,423 (1,050)	173 (6.8)	2.0 (4.3)	139 (4.9)	1/4	4.76	93.9 / 104.9 DB	6.2 (90)
26239	5,000	3/4"	2,032 (1,500)	210 (8.3)	3.1 (6.8)	198 (7.0)	3/8	6.50	94.0 / 105.0 DB	6.2 (90)