



Twin Hammer

Mg Alloy Impact Wrench



Mg alloy

Composite Body

Spring-mounted
Rotor Blade

Lightweight

Durable

Powerful

Magnesium Alloy Housing

24201 1/2"

26205 Mini 3/4"

3-Speed Forward and
Max. Reverse Torque

360° Swivel Air Inlet

26215 3/4"

28215 Mini 1"

28214 1"

28218 1"

28214L 1" Dr. with 6" Anvil

28218-8 1" Dr. with 8" Anvil

Item No.	Speed RPM	Square Drive	Max. Torque Nm/ft-lb	Length mm/inch	Weight kg/lb	Air Consumption LPM / CFM	Air Inlet inch	Vibration m/s ²	Noise Level LpA / LwA	Working Pressure Bar / PSI
24201	8,500	1/2"	1,283 (950)	179 (7.0)	1.7 (3.6)	158 (5.5)	1/4	7.45	93.4 / 104.4 DB	6.2 (90)
26205	8,500	3/4"	1,215 (900)	198 (7.8)	1.9 (4.0)	158 (5.5)	1/4	6.02	93.4 / 104.4 DB	6.2 (90)
26215	6,000	3/4"	2,092 (1,550)	209 (8.2)	3.0 (6.6)	198 (7.0)	3/8	6.80	96.9 / 107.9 DB	6.2 (90)
28215	6,000	1"	2,092 (1,550)	219 (8.6)	3.2 (6.9)	198 (7.0)	3/8	6.51	96.9 / 107.9 DB	6.2 (90)
28214	5,500	1"	3,105 (2,300)	256 (10.0)	5.9 (13)	212 (7.5)	1/2	14.76	95.2 / 106.2 DB	6.2 (90)
28214L	5,500	1"	3,105 (2,300)	417 (16.4)	6.8 (15)	212 (7.5)	1/2	17.60	95.2 / 106.2 DB	6.2 (90)
28218	5,500	1"	3,105 (2,300)	403 (15.9)	6.5 (14.3)	212 (7.5)	1/2	14.76	95.2 / 106.2 DB	6.2 (90)
28218-8	5,500	1"	3,105 (2,300)	616 (24.2)	7.9 (17.2)	212 (7.5)	1/2	17.60	95.2 / 106.2 DB	6.2 (90)