

- **Compact and lightweight**
- **High torque output**
- **Built-in Power Regulator**
- **Controllable throttle provides easy bolt starting.**

Aluminium Impact Wrench




*Ultra
Lightweight*

High Torque

2,600 ft-lb | 2,800 ft-lb

28212L 1" Dr. (8" Anvil, Twin Hammer)

28412L 1" Dr. (8" Anvil, Pinless)



2,600 ft-lb | 2,800 ft-lb

28212 1" Dr. (Twin Hammer)

28412 1" Dr. (Pinless)



29201 1-1/2" Dr. (Twin Hammer)

29201L 1-1/2" Dr. (8" Anvil)

3,200 ft-lb



3,600 ft-lb

29205 1-1/2" Dr. (Twin Hammer)

29205L 1-1/2" Dr. (8" Anvil)



4,000 ft-lb

29206 1-1/2" Dr. (Twin Hammer)

29206L 1-1/2" Dr. (8" Anvil)

Item No.	Speed RPM	Square Drive	Max. Torque Nm/ft-lb	Length mm/inch	Weight kg/lb	Air Consumption LPM / CFM	Air Inlet inch	Working Pressure Bar / PSI
28212	4,800	1"	3,525 (2,600)	370 (14.6)	10.5 (23.1)	178 (6.3)	1/2"	6.2 (90)
28212L	4,800	1"	3,525 (2,600)	570 (22.4)	11.9 (26.2)	178 (6.3)	1/2"	6.2 (90)
28412	4,800	1"	3,796 (2,800)	370 (14.6)	11.0 (24.2)	178 (6.3)	1/2"	6.2 (90)
28412L	4,800	1"	3,796 (2,800)	570 (22.4)	12.5 (27.5)	178 (6.3)	1/2"	6.2 (90)
29201	3,500	1-1/2"	4,336 (3,200)	420 (16.5)	17.1 (37.6)	254 (9.0)	1/2"	6.2 (90)
29201L	3,500	1-1/2"	4,336 (3,200)	575 (22.6)	19.3 (42.5)	254 (9.0)	1/2"	6.2 (90)
29205	2,600	1-1/2"	4,878 (3,600)	435 (17.1)	17.1 (37.6)	254 (9.0)	1/2"	6.2 (90)
29205L	2,600	1-1/2"	4,878 (3,600)	590 (23.2)	20.0 (44.0)	254 (9.0)	1/2"	6.2 (90)
29206	3,500	1-1/2"	5,420 (4,000)	450 (17.7)	17.0 (37.4)	317 (11.2)	1/2"	6.2 (90)
29206L	3,500	1-1/2"	5,420 (4,000)	605 (23.8)	19.3 (42.5)	317 (11.2)	1/2"	6.2 (90)