



Belt Sanders (for Sanding)

- Powerful design for industrial and heavy duty applications
- Great for light material removal, cleaning up rough castings, grinding down welds, light rust removal, deburring parts and other finishing tasks

360° Adjustable Swivel Sanding Arm

Non-slip and Ergonomic Composite Grip

Low Noise

Safety Guard



55027 (20 x 520 mm)

55037 (30 x 540 mm)



55006 (6 x 457 mm)

55017 (10 x 330 mm)

55015 (13 x 457 mm)

55014 (13 x 610 mm)



B-55112K

Contents :

- 1 x Belt Sander **55112**
- 1 x each (#80, #100, #120) Sanding Blet sized 3 x 330 mm
- 2 x each (#80, #100, #120) Sanding Belt sized 6 x 330 mm
- 2 x each (#80, #100, #120) Sanding Belt sized 8 x 330 mm
- 1 x each (#80, #100, #120) Sanding Blet sized 10 x 330 mm
- 1 x each (#80, #100, #120) Sanding Blet sized 12 x 330 mm
- 1 x each (#80, #100, #120) Sanding Blet sized 18 x 330 mm
- 1 x Contact Arm for 3 mm Belt
- 1 x Contact Arm for 3 & 5 mm Belt
- 1 x Contact Arm for 5 & 6 mm Belt
- 3 x Contact Arm for 8 & 10 mm Belt (different shape of arms)
- 1 x Contact Arm for 10 & 12 mm Belt
- 1 x Contact Arm for 18 mm Belt
- 1 x 3 mm Hex. Wrench
- 1 x Blow Mould Case



55126 (10 x 330 mm)

Item No.	Speed RPM	Sanding Paper	Power KW/HP	Length mm/inch	Weight kg/lb	Air Consumption LPM / CFM	Air Inlet inch	Vibration m/s ²	Noise Level LpA / LwA
55006	16,500	6 x 457 mm (1/4" x 18")	0.35 (0.5)	390 (15.4)	0.9 (2.0)	113 (4.0)	1/4	< 2.5	94.0 / 105 DB
55017	16,500	10 x 330 mm (3/8" x 13")	0.35 (0.5)	326 (12.8)	0.9 (2.0)	113 (4.0)	1/4	< 2.5	94.0 / 105 DB
55015	16,500	13 x 457 mm (1/2" x 18")	0.35 (0.5)	390 (15.3)	0.9 (2.0)	113 (4.0)	1/4	< 2.5	94.0 / 105 DB
55014	16,500	13 x 610 mm (1/2" x 24")	0.35 (0.5)	450 (17.7)	1.0 (2.2)	113 (4.0)	1/4	< 2.5	94.0 / 105 DB
55027	16,500	20 x 520 mm (3/4" x 20-1/2")	0.35 (0.5)	407 (16.0)	1.3 (2.9)	113 (4.0)	1/4	< 2.5	94.0 / 105 DB
55037	13,000	30 x 540 mm (1-3/16" x 21-1/4")	0.52 (0.7)	415 (16.3)	1.5 (3.3)	127 (4.5)	1/4	< 2.5	92.8 / 103.8 DB
55112	16,000	10 x 330 mm (3/8" x 13")	0.35 (0.5)	380 (14.9)	2.3 (5.1)	99 (3.5)	1/4	< 2.5	74.0 / 85.0 DB
55126	20,000	10 x 330 mm (3/8" x 13")	0.25 (0.33)	214 (8.4)	0.7 (1.6)	67 (2.4)	1/4	< 2.5	72.3 / 83.3 DB

Belt Sander (for Conditioning)

- **Speed-Reduction Gear** suitable for surface conditioning.
- **Durable and powerful tools** work well to remove coarse grindlines, mill marks or small burrs.
- **Suitable for many different applications** on both wood and metal
- **Accepts Surface Conditioning Belts and Sanding Belt**



- 55027G

(20 x 520 mm)
- 55006G

(6 x 457 mm)
- 55037G

(30 x 540 mm)
- 55017G

(10 x 330 mm)
- 55014G

(13 x 610 mm)



Surface Conditioning Belts



Pipe Belt Sander

- 55610G

(30 x 640 mm)
- 55611G

(40 x 760 mm)



- **Unique design for use on rounded surfaces**
5 ~ 120 mm (0.2" ~ 4.7") in diameter

0.6/0.9 HP Powerful Belt Sander



- **Perfect for Spot Weld Removal** when used with ceramic sanding belts



- Item : Ceramic Sanding Belt
A312SB-C13-04/06/08
- Grit : #40, #60 or #80

- 55113

(10 x 330 mm)
- 55114

(13 x 457 mm)
- 55210

(20 x 520 mm)

Item No.	Speed RPM	Sanding Paper mm/inch	Power KW/HP	Length mm/inch	Weight kg/lb	Air Consumption LPM / CFM	Air Inlet inch	Vibration m/s²	Noise Level LpA / LwA
55006G	4,500	6 x 457 mm (1/4" x 18")	0.35 (0.5)	390 (15.4)	0.9 (2.0)	113 (4.0)	1/4	< 2.5	94.0 / 105.0 DB
55017G	4,500	10 x 330 mm (3/8" x 13")	0.35 (0.5)	326 (12.8)	0.9 (2.0)	113 (4.0)	1/4	< 2.5	94.0 / 105.0 DB
55014G	4,500	13 x 610 mm (1/2" x 24")	0.35 (0.5)	450 (17.7)	1.0 (2.2)	113 (4.0)	1/4	< 2.5	94.0 / 105.0 DB
55027G	4,500	20 x 520 mm (3/4" x 20-1/2")	0.35 (0.5)	407 (16.0)	1.3 (2.9)	113 (4.0)	1/4	< 2.5	94.0 / 105.0 DB
50037G	3,300	30 x 540 mm (1-3/16" x 21-1/4")	0.52 (0.7)	415 (16.3)	1.5 (3.3)	127 (4.5)	1/4	< 2.5	92.8 / 103.8 DB
55610G	3,300	30 x 640 mm (1-3/16" x 25-3/16")	0.52 (0.7)	387 (15.2)	2.1 (4.6)	170 (6.0)	1/4	< 2.5	92.8 / 103.8 DB
55611G	3,300	40 x 760 mm (1-1/2" x 30")	0.52 (0.7)	420 (16.5)	2.3 (5.0)	170 (6.0)	1/4	< 2.5	92.8 / 103.8 DB
55113	18,000	10 x 330 mm (3/8" x 13")	0.45 (0.6)	325 (12.8)	0.8 (1.7)	99 (3.5)	1/4	< 2.5	80.0 / 91.0 DB
55114	18,000	13 x 457 mm (1/2" x 18")	0.45 (0.6)	385 (15.2)	0.8 (1.7)	99 (3.5)	1/4	< 2.5	80.0 / 91.0 DB
55210	18,000	20 x 520 mm (3/4" x 20-1/2")	0.67 (0.9)	396 (15.6)	1.0 (2.1)	108 (3.8)	1/4	< 2.5	80.0 / 91.0 DB