



Polisher



50080

- Geared rotary action with speed control
- Compact size, excellent power to buff and polish motorcycle gas tanks and helmets, small parts, side view mirrors and bumper



50085

- **Mini and compact design** with industrial level quality
- Ergonomic pistol grip with trigger control
- Variable speed trigger for maximum control



3,200 rpm 5,000 rpm

50086 50087

- Easy for small and hard-to-reach jobs, feather edging, light sanding and rust removal
- Lightweight and compact design
- Easy to adjust speed control



5" pad 6" pad

50050 50060

- Suitable for most kinds of polishing jobs to a high gloss professional finish
- 0.55 HP high output motor
- Ergonomic trigger for variable control
- Side handle



50074A

- 3" Extension Angle Buffer
- Ideal for buffing & polishing in small areas
- For quick & easy spot repair on variety of surface



50075

- Soft-grip handle
- Compact and lightweight
- Rear exhaust
- Variable speed safety-lock lever throttle
- Soft-grip handle



3,600 rpm 4,500 rpm

59302L 59302-1L

- 3" Angle Sander / Buffer (Extended Type)
- Low profile suitable for working in tight areas
- Low-noise Design
- Spindle Lock and Speed Regulator
- Rear Swivel Exhaust



3,600 rpm 4,500 rpm

59302 59302-1

- 3" Angle Sander / Buffer
- Low profile suitable for working in tight areas
- Low-noise Design
- Spindle Lock and Speed Regulator
- Rear Swivel Exhaust

Item No.	Speed RPM	Pad mm/inch	Power KW/HP	Spindle Size	Length mm/inch	Weight kg/lb	Air Consumption LPM / CFM	Air Inlet inch	Vibration m/s ²	Noise Level LpA / LwA
50080	2,400	75 (3)	0.26 (0.35)	5/16"-24	110 (4.3)	0.75 (1.65)	65 (2.3)	1/4	< 2.5	76.3 / 87.3 DB
50085	3,200	75 (3)	0.22 (0.30)	5/16"-24	162 (6.4)	0.78 (1.70)	57 (2.0)	1/4	< 2.5	88.4 / 99.4 DB
50086	3,200	75 (3)	0.30 (0.40)	3/8"-24	209 (8.2)	0.72 (1.58)	113 (4.0)	1/4	< 2.5	76.9 / 87.9 DB
50087	5,000	75 (3)	0.30 (0.40)	3/8"-24	209 (8.2)	0.73 (1.60)	113 (4.0)	1/4	< 2.5	79.1 / 90.1 DB
50050	3,000	125 (5)	0.41 (0.55)	Outer 5/8"-11 (M) + Inner 5/16"-24(F)	205 (8.1)	1.12 (2.46)	103 (3.7)	1/4	< 2.5	86.8 / 97.8 DB
50060	3,000	150 (6)	0.41 (0.55)	Outer 5/8"-11 (M) + Inner 5/16"-24(F)	205 (8.1)	1.12 (2.46)	103 (3.7)	1/4	< 2.5	86.8 / 97.8 DB
50074A	2,300	75 (3)	0.22 (0.30)	5/16"-24	170 (6.7)	0.70 (1.54)	60 (2.1)	1/4	< 2.5	85.0 / 96.0 DB
50075	2,500	180 (7)	0.52 (0.70)	M14 x 2.0	305 (12)	2.20 (4.84)	89 (3.1)	1/4	< 2.5	82.6 / 93.6 DB
59302	3,600	75 (3)	0.26 (0.35)	1/4"-20	207 (8.1)	0.70 (1.54)	73.6 (2.6)	1/4	< 2.5	84.0 / 95.0 DB
59302-1	4,500	75 (3)	0.26 (0.35)	1/4"-20	207 (8.1)	0.70 (1.54)	73.6 (2.6)	1/4	< 2.5	84.0 / 95.0 DB
59302L	3,600	75 (3)	0.26 (0.35)	1/4"-20	261 (10.3)	0.75 (1.65)	73.6 (2.6)	1/4	< 2.5	84.0 / 95.0 DB
59302-1L	4,500	75 (3)	0.26 (0.35)	1/4"-20	261 (10.3)	0.75 (1.65)	73.6 (2.6)	1/4	< 2.5	84.0 / 95.0 DB