



3 mm orbit

51485

- Easy for small and hard-to-reach jobs, feather edging, light sanding and rust removal
- Lightweight and compact
- Easy to adjust speed



Direct Drive

54085

- Pad : 3"
- Easy for small and hard-to-reach jobs, feather edging, light sanding and rust removal
- Lightweight and compact
- Easy to adjust speed



Direct Drive

54030

- Rugged design for rapid finishing and polishing
- Heavy duty construction
- Gearless design for easy maintenance
- **7 Degree offset** ergonomic design for greater control



Bevel Gear

54212

- Rugged design for rapid metal removal, deburring, finishing and polishing
- Heavy duty construction for high durability and quality
- Durable and Long Lasting Gear Set

**58006**

- Angle Head with Rubber Cover to avoid scratch
- Sanding in random pattern to remove defect
- Rear exhaust muffler design reduces sound levels.



5 mm orbit

Non-Vacuum Central-Vacuum

57361-H**57362-H**

- 6" Gear-driven Orbital Sander
- Rough removal and smooth sanding on metal, solid surfaces, etc.
- Remove a large amount of filler materials such as glue and epoxy.

**59033**

- Excellent for roughing in body filler, rust removal and weld smoothing
- Low Profile suitable for working in confined spaces
- Spindle lock design



5"

59034R

7"

59035R

- 2.3 HP powerful and high-performance motor
- Spindle lock button for easy and quick wheel change
- Removable side-handle on either side

Item No.	Speed RPM 	Pad mm/inch 	Power KW/HP kW	Spindle Size 	Length mm/inch 	Weight kg/lb kg	Air Consumption LPM / CFM 	Air Inlet inch 	Vibration m/s ² 	Noise Level LpA / LwA
51485	18,000	75 (3)	0.22 (0.3)	5/16"-24	176 (6.9)	0.65 (1.43)	57 (2.0)	1/4	8.39	89.5 / 100.5 DB
54085	18,000	75 (3)	0.22 (0.3)	M6	187 (7.4)	0.59 (1.30)	57 (2.0)	1/4	2.82	89.7 / 100.7 DB
54030	25,000	75 (3)	0.30 (0.4)	1/4"-20	206 (8.1)	0.57 (1.25)	113 (4.0)	1/4	2.89	73.4 / 84.4 DB
54212	20,000	50 (2)	0.30 (0.4)	1/4"-20	180 (7.1)	0.50 (1.10)	113 (4.0)	1/4	2.90	74.8 / 85.8 DB
58006	7,500	30 (1-1/4)	0.22 (0.3)	M10 x 1.25	168 (6.6)	0.63 (1.40)	17 (0.62)	1/4	< 2.5	72.2 / 83.2 DB
57361-H	1,000	150 (6)	0.45 (0.6)	-	260 (10.2)	1.60 (3.52)	85 (3.0)	1/4	< 2.5	82.0 / 93.0 DB
57362-H	1,000	150 (6)	0.45 (0.6)	-	280 (11.7)	1.60 (3.52)	85 (3.0)	1/4	< 2.5	82.0 / 93.0 DB
59033	4,500	180 (7)	0.97 (1.3)	M14 x 2.0 5/8"-11	328 (12.9)	2.30 (5.06)	108 (3.8)	1/4	< 2.5	90.0 / 101.0 DB
59034R	12,000	125 (5)	1.72 (2.3)	M14 x 2.0	265 (10.5)	1.55 (3.41)	195 (6.9)	3/8	5.2	95.0 / 106.0 DB
59035R	8,500	180 (7)	1.72 (2.3)	M14 x 2.0	291 (11.5)	1.60 (3.52)	195 (6.9)	3/8	5.2	95.0 / 106.0 DB