



Industrial Reversible Air Drill

Reversible Bar on top
easy one-handed operation



3/8", 0.6HP

33205



33110

33111

33112

3/8", 0.73HP

33210



33211



33113

33114

1/2", 0.6HP

34205



34206



34110

34111

1/2", 0.73HP

34210



34212



34112

34113

34114

34115

1/4", 0.6HP

32110

32112

1/4", 0.73HP

32113

32114

- Powerful, durable
- Reversible drill
- Suitable for casting in any ferrous or non-ferrous foundry

Item No.	Speed RPM 	Reversible or not 	Chuck Cap. mm/inch 	Power KW/HP kW	Length mm/inch 	Weight kg/lb kg	Air Consumption LPM / CFM
33205	2,100	V	3/8"	0.45 (0.6)	215 (8.5)	1.04 (2.3)	113 (4.0)
34205	350	V	1/2"	0.45 (0.6)	252 (9.9)	1.40 (3.1)	113 (4.0)
34206	700	V	1/2"	0.45 (0.6)	252 (9.9)	1.40 (3.1)	113 (4.0)
32110	4,000	-	1/4"	0.45 (0.6)	185 (7.3)	1.0 (2.2)	113 (4.0)
32111	5,600	-	1/4"	0.45 (0.6)	185 (7.3)	0.95 (2.1)	113 (4.0)
32112	25,000	-	1/4"	0.45 (0.6)	225 (8.9)	0.75 (1.7)	113 (4.0)
33110	2,800	-	3/8"	0.45 (0.6)	200 (7.9)	1.0 (2.2)	113 (4.0)
33111	4,000	-	3/8"	0.45 (0.6)	200 (7.9)	1.0 (2.2)	113 (4.0)
33112	5,600	-	3/8"	0.45 (0.6)	200 (7.9)	0.95 (2.1)	113 (4.0)
34110	500	-	1/2"	0.45 (0.6)	240 (9.4)	1.4 (3.1)	113 (4.0)
34111	700	-	1/2"	0.45 (0.6)	240 (9.4)	1.4 (3.1)	113 (4.0)
33210	1,500	V	3/8"	0.54 (0.73)	234 (9.2)	1.1 (2.4)	113 (4.0)
33211	2,800	V	3/8"	0.54 (0.73)	234 (9.2)	1.1 (2.4)	113 (4.0)
34210	250	V	1/2"	0.54 (0.73)	272 (10.7)	1.5 (3.3)	113 (4.0)
34212	500	V	1/2"	0.54 (0.73)	272 (10.7)	1.6 (3.5)	113 (4.0)
32113	3,500	-	1/4"	0.54 (0.73)	204 (8.0)	1.05 (2.3)	113 (4.0)
32114	21,000	-	1/4"	0.54 (0.73)	225 (8.9)	0.75 (1.7)	113 (4.0)
33113	2,600	-	3/8"	0.54 (0.73)	218 (8.6)	1.1 (2.4)	113 (4.0)
33114	3,500	-	3/8"	0.54 (0.73)	218 (8.6)	1.1 (2.4)	113 (4.0)
34112	600	-	1/2"	0.54 (0.73)	258 (10.2)	1.5 (3.3)	113 (4.0)
34113	800	-	1/2"	0.54 (0.73)	258 (10.2)	1.5 (3.3)	113 (4.0)
34114	2,600	-	1/2"	0.54 (0.73)	232 (9.1)	1.1 (2.4)	113 (4.0)
34115	3,500	-	1/2"	0.54 (0.73)	232 (9.1)	1.1 (2.4)	113 (4.0)