



Industrial Screwdriver

- **Durable planetary gear**
- **Ergonomic grip for comfortable use**
- **Low-noise muffler, Power up to 0.6 HP or 0.73 HP**



Reversible Bar on top
easy one-handed operation



Stall Clutch
0.6 HP

64100 0.6 HP, 22 Nm

64101 0.6 HP, 18 Nm



Stall Clutch
0.6 HP

64102 0.6 HP, 10 Nm

64103 0.6 HP, 7.0 Nm



Stall Clutch
0.73 HP

64500 0.73 HP, 27 Nm

64501 0.73 HP, 17 Nm

64502 0.73 HP, 9.0 Nm



Positive Clutch
0.6 HP

64104 0.6 HP, 6.2 Nm

64105 0.6 HP, 4.5 Nm



Positive Clutch
0.73 HP

64503 0.73 HP, 16.4 Nm

64504 0.73 HP, 9.0 Nm

Item No.	Speed RPM	Power KW/HP	Chuck mm/inch	Torque Nm/in-lb	Length mm/inch	Weight kg/lb	Air Consumption LPM / CFM	Air Inlet inch	Working Pressure Bar / PSI
64100	350	0.45 (0.6)	1/4" Hex	22 (194)	230 (9.1)	1.1 (2.4)	113 (4.0)	1/4	6.2 (90)
64101	700	0.45 (0.6)	1/4" Hex	18 (159)	230 (9.1)	1.1 (2.4)	113 (4.0)	1/4	6.2 (90)
64102	2,000	0.45 (0.6)	1/4" Hex	10 (88)	200 (7.9)	0.9 (2.0)	113 (4.0)	1/4	6.2 (90)
64103	4,000	0.45 (0.6)	1/4" Hex	7.0 (62)	200 (7.9)	0.9 (2.0)	113 (4.0)	1/4	6.2 (90)
64104	1,800	0.45 (0.6)	1/4" Hex	6.2 (55)	195 (7.7)	0.9 (2.0)	113 (4.0)	1/4	6.2 (90)
64105	2,800	0.45 (0.6)	1/4" Hex	4.5 (40)	195 (7.7)	0.9 (2.0)	113 (4.0)	1/4	6.2 (90)
64500	250	0.54 (0.73)	1/4" Hex	27 (258)	250 (9.8)	1.2 (2.6)	113 (4.0)	1/4	6.2 (90)
64501	450	0.54 (0.73)	1/4" Hex	17 (150)	250 (9.8)	1.2 (2.6)	113 (4.0)	1/4	6.2 (90)
64502	2,700	0.54 (0.73)	1/4" Hex	9.0 (80)	225 (8.9)	1.0 (2.2)	113 (4.0)	1/4	6.2 (90)
64503	1,450	0.54 (0.73)	1/4" Hex	16.4 (145)	220 (8.7)	1.0 (2.2)	113 (4.0)	1/4	6.2 (90)
64504	2,000	0.54 (0.73)	1/4" Hex	9.0 (80)	220 (8.7)	1.0 (2.2)	113 (4.0)	1/4	6.2 (90)