



Air Saw & Air Riveter

Less Vibration



80037 Air Saw (10mm stroke)

- Speed: 10,000 BPM
- Stroke: 10 mm (0.4")
- High power to cut off material easily
- Adjustable Guide to preset cutting depth
- Ergonomic design for comfort handling

80400 Air Saw/File (6mm stroke)

- Speed: 10,000 BPM
- Stroke: 6 mm (0.23")
- Power: 0.15 KW (0.2 HP)
- Ergonomic design for comfort handling

82124J

- Max. Rivet Cap. : 4.8 mm
- Non-vacuum Type
- Size of Nosepiece : 2.4 mm, 3.2 mm, 4.0 mm & 4.8 mm (3/32", 1/8", 5/32" & 3/16")



Working Capacity:

- Up to M10 in all material
- Up to M12 in Al. & steel rivet nut



82126J 82140J

- Max. Rivet Cap. :
82126J : 4.8 mm
82140J : 6.4 mm
- Non-vacuum Type
- Size of Nosepiece : 2.4 mm, 3.2 mm, 4.0 mm, 4.8 mm, 5.6 mm & 6.4 mm (3/32", 1/8", 5/32", 3/16", 7/32" & 1/4") for 82140J

82126J-V 82140J-V

- Max. Rivet Cap. :
82126J-V : 4.8 mm
82140J-V : 6.4 mm
- Vacuum Type
- Size of Nosepiece : 2.4 mm, 3.2 mm, 4.0 mm, 4.8 mm, 5.6 mm & 6.4 mm (3/32", 1/8", 5/32", 3/16", 7/32" & 1/4") for 82140J-V

B-87950K Air Hydraulic Spin Pull Tool Kit

- Compact, powerful and durable design
- Adjustable stroke to ensure optimum insert deformation
- Capacity : M3 ~ M12, Max. Stroke : 6.0 mm
- Max. Traction Power : 2075 kgf (4565 lbs)

Contents :

- 1 x 87950 Air Hydraulic Spin Pull Tool
- 7 x Tie Rod Kits (M3, M4, M5, M6, M8, M10 & M12)
- 7 x Tie Rods (M3, M4, M5, M6, M8, M10 & M12)

Item No.	Traction Power kg / lb	Rivet Cap. mm/inch	Stroke mm/inch	Speed BPM	Stroke mm/inch	Length mm/inch	Weight kg / lb	Air Inlet inch	Working Pressure Bar / PSI
80037	-	-	-	10,000	10 (0.4)	193 (7.6)	0.7 (1.5)	1/4	6.2 (90)
80040	-	-	-	10,000	6 (0.23)	195 (7.7)	0.56 (1.2)	1/4	6.2 (90)
82124J	900 (1,980)	2.4 ~ 4.8 (3/32 ~ 3/16)	16 (0.63)	-	-	270 (10.6)	1.5 (3.3)	1/4	6.2 (90)
82126J	880 (1,940)	2.4 ~ 4.8 (3/32 ~ 3/16)	14 (0.55)	-	-	270 (10.6)	1.5 (3.3)	1/4	6.2 (90)
82140J	1,400 (3,080)	2.4 ~ 6.4 (3/32 ~ 1/4)	19 (0.75)	-	-	325 (12.8)	2.2 (4.8)	1/4	6.2 (90)
82126J-V	880 (1,940)	2.4 ~ 4.8 (3/32 ~ 3/16)	14 (0.55)	-	-	270 (10.6)	1.5 (3.3)	1/4	6.2 (90)
82140J-V	1,400 (3,080)	2.4 ~ 6.4 (3/32 ~ 1/4)	19 (0.75)	-	-	325 (12.8)	2.1 (4.7)	1/4	6.2 (90)
B-87950K	2,075 (4,565)	M3 ~ M12	6.0 (0.23)	-	-	310 (12.2)	2.3 (5.2)	1/4	6.2 (90)