



Impact Wrench

Twin Hammer



286.5 mm (11.3")



3/4" 6" Anvil 1" 6" Anvil
26235 26235L 28235 28235L

- Compact Size
- Light weight
- High torque output
- Built-in Power Regulator
- Controllable throttle provides easy bolt starting.



24212B

- Handle air exhaust
- High nut breaking torque
- Durable and powerful clutch system



24217

- Powerful torque up to 900 Nm (670 ft-lb) !
- Durable twin hammer mechanism
- Comfortable cushion grip
- Three power setting in forward and full power in reverse



3/4" 6" Anvil 1" 6" Anvil
26208 26208L 28208 28208L

- Most powerful and compact, deliver best Power-to-Size ratio in this class
- 3-position power management in forward and 3-position in reverse
- Handle exhaust

Item No.	Speed RPM 	Square Drive 	Max. Torque Nm/ft-lb 	Length mm/inch 	Weight kg/lb 	Air Consumption LPM / CFM 	Air Inlet inch 	Working Pressure Bar / PSI
26235	7,500	3/4"	1,898 (1,400)	286.5 (11.3)	4.5 (9.9)	160 (5.6)	3/8	6.2 (90)
26235L	7,500	3/4"	1,627 (1,200)	434.5 (17.0)	5.0 (11.0)	160 (5.6)	3/8	6.2 (90)
28235	7,500	1"	2,034 (1,500)	288.6 (11.4)	4.6 (10.1)	160 (5.6)	3/8	6.2 (90)
28235L	7,500	1"	1,763 (1,300)	441.6 (17.4)	5.4 (11.9)	160 (5.6)	3/8	6.2 (90)
24212B	8,000	1/2"	745 (550)	185 (7.3)	2.6 (5.7)	113 (4.0)	1/4	6.2 (90)
24217	9,500	1/2"	900 (670)	190 (7.5)	2.4 (5.3)	125 (4.4)	1/4	6.2 (90)
26208	7,500	3/4"	1,898 (1,400)	210 (8.3)	3.9 (8.6)	119 (4.2)	3/8	6.2 (90)
26208L	7,500	3/4"	1,627 (1,200)	358 (14.1)	4.7 (10.3)	119 (4.2)	3/8	6.2 (90)