




Spindle - Lock Grinder / Cutter


- **Spindle Lock System** - quick and easy change abrasive
- **Low-noise Muffler Design, Power up to 0.7 HP**



Spindle Lock / Release



Pull Ring and Lock



Pull Ring and Release



Low-noise Muffler

0.35 HP

71310

0.50 HP

71210

0.70 HP

71110

Spindle Lock



0.35 HP

74310

0.50 HP

74210

0.70 HP

74110



0.50 HP

71210-3



0.70 HP

71112



0.7 HP

74112



0.7 HP

75112 4"

(Spindle: M10*1.5)

75112-4 4", Ext.

(Spindle: M10*1.5)



1.0 HP

75019 4" wheel

(Spindle: M10*1.5)

75023 5" wheel

(Spindle: M14*2.0)

Item No.	Speed RPM	Power KW/HP	Collet mm/inch	Wheel mm / inch	Length mm/inch	Weight kg/lb	Air Inlet inch	Air Consumption LPM / CFM	Vibration m/s ²	Noise Level LpA / LwA
71110	20,000	0.52 (0.70)	6 (1/4)	-	214 (8.4)	0.8 (1.8)	1/4	102 (3.6)	< 2.5	80.9 / 91.9 DB
71112	19,000	0.52 (0.70)	6 (1/4)	-	330 (13.0)	1.1 (2.4)	1/4	102 (3.6)	< 2.5	80.5 / 91.5 DB
71210	22,000	0.37 (0.50)	6 (1/4)	-	204 (8.0)	0.7 (1.6)	1/4	93 (3.3)	< 2.5	79.9 / 90.9 DB
71210-3	20,000	0.37 (0.50)	6 (1/4)	-	250 (9.8)	0.8 (1.8)	1/4	93 (3.3)	< 2.5	81.0 / 92.0 DB
71310	25,000	0.26 (0.35)	6 (1/4)	-	185 (7.3)	0.5 (1.2)	1/4	57 (2.0)	3.40	76.0 / 87.0 DB
74110	18,000	0.52 (0.70)	6 (1/4)	-	192 (7.5)	0.9 (2.1)	1/4	102 (3.6)	< 2.5	80.3 / 91.3 DB
74112	18,000	0.52 (0.70)	6 (1/4)	-	295 (11.6)	1.1 (2.4)	1/4	102 (3.6)	5.26	78.3 / 89.3 DB
74210	19,000	0.37 (0.50)	6 (1/4)	-	182 (7.16)	0.8 (1.9)	1/4	93 (3.3)	6.04	78.8 / 89.8 DB
74310	20,000	0.26 (0.35)	6 (1/4)	-	169 (6.7)	0.6 (1.3)	1/4	57 (2.0)	3.48	74.2 / 85.2 DB
75112	19,000	0.52 (0.70)	-	100 (4)	260 (10.2)	1.3 (2.9)	1/4	108 (3.8)	3.29	85.2 / 96.2 DB
75112-4	18,500	0.52 (0.70)	-	100 (4)	355 (14.0)	1.5 (3.4)	1/4	108 (3.8)	4.94	85.4 / 96.4 DB
75019	14,000	0.75 (1.0)	-	100 (4)	388 (15.2)	2.1 (4.7)	1/4	99 (3.5)	-	-
75023	14,000	0.75 (1.0)	-	125 (5)	388 (15.2)	2.1 (4.7)	1/4	99 (3.5)	-	-