



Air Screwdriver



- Direct Drive
- 0.3 HP

64300

- Direct drive mechanism for quick fastening operations
- Suit for high volume fasteners assembly
- Reversible



- Direct Drive
- 0.3 HP

64301

- Direct drive mechanism for quick fastening operations
- Rear exhaust
- Reversible



Direct Drive

64201

- Direct drive mechanism for quick fastening operations
- Ergonomic pistol grip
- Ideal applications for self-tapping and wood screws
- Reversible



Positive Clutch

62302

- Positive Clutch
- Lightweight and compact
- Built-in muffler for noise reduction
- Quick change bit retainer



Cushion Clutch

62405

- Cushion Clutch
- External Clutch Adjustable
- Lightweight and compact
- Built-in muffler
- Quick change bit retainer



Cushion Clutch

62420

- Cushion Clutch
- Torque Adjustable
- One-hand push button power regulator
- Reversible

Item No.	Speed RPM 	Chuck mm/inch 	Torque Nm/in-lb 	Length mm/inch 	Weight kg/lb 	Air Consumption LPM / CFM 	Air Inlet inch 	Working Pressure Bar / PSI P
64300	2,300	1/4" Hex	5.0 (44.2)	210 (8.5)	0.8 (1.9)	113 (4.0)	1/4	6.2 (90)
64301	1,900	1/4" Hex	5.5 (48.6)	220 (8.6)	1.1 (2.4)	113 (4.0)	1/4	6.2 (90)
64201	3,000	1/4" Hex	7.0 (62.0)	140 (5.5)	0.8 (1.9)	85 (3.0)	1/4	6.2 (90)
62302	1,800	1/4" Hex	13 (115)	190 (7.5)	1.1 (2.4)	142 (5.0)	1/4	6.2 (90)
62405	1,800	1/4" Hex	2.3 ~ 13 (20 ~ 115)	215 (8.5)	1.2 (2.6)	85 (3.0)	1/4	6.2 (90)
62420	1,800	1/4" Hex	5 ~ 13 (45 ~ 115)	265 (10.4)	1.2 (2.6)	73 (2.6)	1/4	6.2 (90)