

Super Duty Grinder



0.45 HP

70010 (Roll) **70010L** (lever)

Speed	20,000 rpm
Power	0.34 kw (0.45 hp)
Collet	6 mm (1/4")



0.45 HP

70010-5 (Roll) **70010L-5** (lever)

Speed	18,000 rpm
Power	0.34 kw (0.45 hp)
Collet	6 mm (1/4")



0.9 HP

70022 (Roll) **70022L** (lever)

Speed	18,000 rpm
Power	0.67 kw (0.9 hp)
Collet	6 mm (1/4")



0.9 HP (4", 5")
2.0 HP (7")

75005 **75006** **75105**

Speed	13,600 rpm	11,000 rpm	7,600 rpm
Power	0.67 kw (0.9 hp)		(2.0 hp)
Wheel Cap.	(4") 100mm	(5") 125 mm	(7") 180mm



1.4 HP

75008L **75009L**

Speed	12,000 rpm	12,000 rpm
Power	1.04 kw (1.4 hp)	
Wheel Cap.	(4") 100mm	(5") 125 mm



2.3 HP

75033R **75037R**

Speed	12,000 rpm	7,600 rpm
Power	1.72 kw (2.3 hp)	
Wheel Cap.	(5") 125 mm	(7") 180 mm

Item No.	Speed RPM 	Power KW/HP kW	Collet mm/inch 	Spindle Size 	Wheel mm/inch 	Length mm/inch 	Weight kg/lb kg	Air Inlet inch 	Air Consumption LPM / CFM 	Working Pressure Bar / PSI P
70010	20,000	0.34 (0.45)	6 (1/4)	-	-	175 (6.9)	0.7 (1.5)	1/4	127 (4.5)	6.2 (90)
70010L	20,000	0.34 (0.45)	6 (1/4)	-	-	165 (6.5)	0.6 (1.3)	1/4	127 (4.5)	6.2 (90)
70010-5	18,000	0.34 (0.45)	6 (1/4)	-	-	330 (13.0)	1.1 (2.4)	1/4	127 (4.5)	6.2 (90)
70010L-5	18,000	0.34 (0.45)	6 (1/4)	-	-	320 (12.6)	1.1 (2.4)	1/4	127 (4.5)	6.2 (90)
70022	18,000	0.67 (0.9)	6 (1/4)	-	-	200 (7.9)	1.2 (2.6)	1/4	255 (9.0)	6.2 (90)
70022L	18,000	0.67 (0.9)	6 (1/4)	-	-	195 (7.6)	1.2 (2.6)	1/4	255 (9.0)	6.2 (90)
75005	13,600	0.67 (0.9)	M8 x 1.25 or 3/8"-24		100 (4)	260 (10.2)	1.7 (3.7)	1/4	133 (4.7)	6.2 (90)
75006	11,000	0.67 (0.9)	M8 x 1.25 or 3/8"-24 or 5/8"-11		125 (5)	260 (10.2)	2.1 (4.6)	1/4	133 (4.7)	6.2 (90)
75105	7,600	1.50 (2.0)	M10 x 1.5 or M14 x 2.0 or 5/8"-11		180 (7)	292 (11.5)	3.8 (8.3)	1/4	225 (7.9)	6.2 (90)
75008L	12,000	1.04 (1.4)	M10 x 1.5		100 (4)	214 (8.4)	1.6 (3.5)	3/8	184 (6.5)	6.2 (90)
75009L	12,000	1.04 (1.4)	M10 x 1.5 or M14 x 2.0		125 (5)	214 (8.4)	1.7 (3.7)	3/8	184 (6.5)	6.2 (90)
75033R	12,000	1.72 (2.3)	M14 x 2.0 or 5/8"-11		125 (5)	234 (9.2)	1.8 (4.0)	3/8	195 (6.9)	6.2 (90)
75037R	7,600	1.72 (2.3)	M14 x 2.0 or 5/8"-11		180 (7)	234 (9.2)	2.0 (4.4)	3/8	195 (6.9)	6.2 (90)