



NeuTorq Tool Series

- **Intelligent system to ensure each fasten is accurately completed**
- **Less damage to the tool, socket and bolt assembly**
- **Quiet operation, fatigue-reduced and increased safety design**
- **Free running torque setting and fastening torque detection**
- **Accuracy 5 % • $CmK \geq 1.67$**
- **Calibration certification according to the international standard**

Torque Controller

- Direct Drive
- 0.3 HP



D64301

1/4" Air Screwdriver

CPU control panel

- **Target torque setting in free running**
- **Fastening torque**
- **Accept / Reject light**
- **Low Battery message**



- Direct Drive
- 0.3 HP

D64300

1/4" Air Screwdriver



- Auto Shut off
- Swivel Exhaust

D65002T

1/4" Oil Pulse Screwdriver



Direct Drive


D64201

1/4" Air Screwdriver

Item No.	Speed RPM	Chuck mm/inch	Torque Range Nm/in-lb	Length mm/inch	Weight kg/lb	Air Consumption LPM / CFM	Vibration m/s ²	Noise Level LpA / LwA	Working Pressure Bar / PSI
D64201	3,000	1/4" Hex	2.5~7.0 (22~62)	140 (5.5)	0.8 (1.9)	85 (3.0)	< 2.5	86 / 97 DB	6.2 (90)
D64300	2,300	1/4" Hex	2.0~5.0 (17.7~44.2)	210 (8.5)	0.8 (1.9)	113 (4.0)	< 2.5	81 / 92 DB	6.2 (90)
D64301	1,900	1/4" Hex	2.5~5.5 (22.0~48.6)	220 (8.6)	1.1 (2.4)	113 (4.0)	< 2.5	81 / 92 DB	6.2 (90)
D65002T	5,800	1/4" Hex	16~18 (141.6~159)	182 (7.17)	1.0 (2.3)	85 (3.0)	2.8	85 DB	6.2 (90)



NeuTorq Tool Series



- Direct Drive
- 0.3 HP



D23000 3/8" Direct Drive Wrench

Torque Controller

CPU control panel

- Target torque setting in free running
- fastening torque
- Accept / Reject light
- Low Battery message



- Auto Shut off
- Swivel Exhaust

D25002T

3/8" Oil Pulse Wrench

Item No.	Speed RPM	Torque Range Nm/in-lb	Square Drive	Length mm/inch	Weight kg/lb	Air Consumption LPM / CFM	Vibration m/s ²	Noise Level LpA / LwA	Working Pressure Bar / PSI
D23000	1900	2.5~5.5 (22~48.6)	3/8"	220 (8.6)	1.10 (2.4)	113 (4.0)	< 2.5	81 / 92 DB	6.2 (90)
D25002T	5800	16~18 (141.6~159)	3/8"	178 (7.0)	1.06 (2.3)	85 (3.0)	2.8	85 DB	6.2 (90)

Torque Calibration Analyser

- Suitable for hand torque wrenches and power tools
- Unit : ft-lb, Nm
- Mode : peak, track
- Power : 110 V ~ 240 V
- Working Temperature : - 20°C ~ 70°C



L-TCA0010E 1.0 ~ 10 Nm (0.7 ~ 7.4 ft-lb)

L-TCA0050E 5.0 ~ 50 Nm (3.7 ~ 36 ft-lb)



L-TCA0500E 50 ~ 500 Nm (36 ~ 369 ft-lb)