



NeuTorq Tool Series

- *Intelligent system to ensure each fasten is accurately completed*
- *Less damage to the tool, socket and bolt assembly*
- *Quiet operation, fatigue-reduced and increased safety design*
- *Free running torque setting and fastening torque detection*
- **Accuracy 5 % • $CmK \geq 1.67$**
- *Calibration certification according to the international standard*



Torque Controller

CPU control panel

- *Target torque setting in free running*
- *Fastening torque*
- *Accept / Reject light*
- *Low Battery message*



- Auto Shut off
- Swivel Exhaust

D65002T

1 / 4" Oil Pulse Screwdriver



- Direct Drive

D64201

1 / 4" Air Screwdriver



- Direct Drive
- 0.3 HP

D64301

1 / 4" Air Screwdriver



- Auto Shut off
- Swivel Exhaust

D25002T

3 / 8" Oil Pulse Wrench



- Direct Drive
- 0.3 HP

D23000

3 / 8" Direct Drive Wrench

Item No.	Speed RPM 	Chuck mm/inch 	Square Drive 	Torque Range Nm/in-lb 	Length mm/inch 	Weight kg/lb 	Air Consumption LPM / CFM 	Vibration m/s² 	Noise Level LpA / LwA 	Working Pressure Bar / PSI
D64201	3,000	1/4" Hex	-	7.0 (62)	140 (5.5)	0.8 (1.9)	85 (3.0)	< 2.5	86 / 97 DB	6.2 (90)
D64301	1,900	1/4" Hex	-	5.5 (48.6)	220 (8.6)	1.1 (2.4)	113 (4.0)	< 2.5	81 / 92 DB	6.2 (90)
D65002T	5,800	1/4" Hex	-	18 (159)	182 (7.17)	1.0 (2.3)	85 (3.0)	2.8	85 DB	6.2 (90)
D25002T	5,800	-	3/8"	18 (159)	178 (7.0)	1.0 (2.3)	85 (3.0)	2.8	85 DB	6.2 (90)
D23000	1,900	-	3/8"	5.5 (48.6)	220 (8.6)	1.1 (2.4)	113 (4.0)	< 2.5	81 / 92 DB	6.2 (90)