


NeuTorq **AIR** Impact Wrench

- Quick and Easy to Use
- Digital Display for Tightening Torque
- Indicator Lights
- Pressure Control



Forward
Tightening Torque :
90 Nm (65 ft-lb)
110 Nm (80 ft-lb)
135 Nm (100 ft-lb)
160 Nm (118 ft-lb)

Reverse
Max. Torque :
880 Nm (650 ft-lb)



24290L 1/2" NeuTorq Impact Wrench (2" Anvi)

- Easy Change Direction in Forward and Reverse
- Reference Tightening Torque Setting for Easy Use
- Composite and lightweight
- Feather trigger for smooth operation
- 360° swivel air inlet
- Easy maintenance for one-piece valve body



24290 1/2" NeuTorq Impact Wrench

Item No.	Speed RPM	Square Drive	Length mm/inch	Weight kg/lb	Air Consumption LPM / CFM	Air Inlet inch	Vibration m/s ²	Noise Level LpA / LwA	Working Pressure Bar / PSI
24290	7,500	1/2"	197 (7.8)	2.6 (5.7)	132 (4.6)	1/4	6.23	95.5 / 106.5	6.2 (90)
24290L	7,500	1/2"	248 (9.8)	2.7 (5.9)	132 (4.6)	1/4	7.22	95.5 / 106.5	6.2 (90)

Torque Calibration Analyser

- Suitable for impact wrenches
- Accuracy : $\pm 1\%$
- Unit : ft-lb, in-lb, Nm, kg-cm, kg-m
- Mode : peak, track
- Power : 110 V ~ 240 V
- Working Temperature : - 20°C ~ 70°C



E-TCA050

Range : 5.0 ~ 50 Nm (3.7 ~ 36 ft-lb)



E-TCA0500

Range : 50 ~ 500 Nm (37 ~ 368 ft-lb)