



Index No.		Description	Quantity
1	H66-B25	M4 x 25mm Flat Head Tap Screw	2
2	B09-A11	Cover	1
3	H70-A01	O-Ring (1 x ID4)	1
4	Y01-A14	Digital Gauge	1
5	H72-A10	STW-10 External Stop Ring	1
6	H70-P05	O-Ring P05	1
7	Y01-A66	Housing Assy	1
8	P01-A18	Coupling	1
9	H70-P07	O-Ring P07	2
10	V02-A04	Regulator	1
11	P01-A16	Coupling	1
12	P01-A17	Coupling Nut	1

Manual for Digital Pressure Gauge

Specifications

* Working Pressure Range :

Unit	Pressure Range	Resolution
PSI	0 ~ 99.8	0.2
BAR	0 ~ 6.88	0.02

- * Medium : Compressed Air
- * Voltage : 3V DC Battery
- * Battery Life : 1,500 hours (continously)
- * Electric Current : < 1.0 mA
- * Operating Temperature : 0 ~ 45 °C (32 ~ 115 °F)
- * Storage Temperature : -10 ~ 75 °C (15 ~ 165 °F)
- * Accuracy : +(-) 2%



Operation

ON / OFF		<p>* Power On : Press the "ON" button.</p> <p>* Turn Off : Press the "ON" button, or the gauge will automatically shut off after the preset time.</p>
Modification of Preset Function		
* Note : Please ensure to disconnect the air hose from the tool before modification.		
a	Function Selection	<p>* Turn on the gauge . Then, press the "ON" button for 3 seconds.</p> <p> Release "ON" → 3 Sec → 3 Sec → 3 Sec → Fail to Modify. Try Again.</p> <p>Press "ON" to select the function item while it is showing on the LCD. Please turn on the gauge again in case you miss the selection.</p>
b	Zero	<p>* Refer to "a" to select the function item .</p> <p> → Press "ON" → → Press "ON" → → Press "ON" → Final Set Up.</p> <p> Fail to Modify. Try Again.</p>
c	Shut-off Time	<p>* Refer to "a" to select the function item . Default : 180 sec.</p> <p> → 3 Sec → 3 Sec → 3 Sec → → Fail to Modify. Try Again.</p> <p>Four cycles</p> <p>Press "ON" to select the time while it is showing on the LCD. Please turn on the gauge again in case you miss the selection.</p> <p> Final Set Up.</p>
d	Switch of Unit Mode	<p>* Refer to "a" to select the function item . Default : Bar</p> <p> → 3 Sec → → Fail to Modify. Try Again.</p> <p>Two cycles</p> <p>Press "ON" to select the unit mode while it is showing on the LCD. Please turn on the gauge again in case you miss the selection.</p> <p> Final Set Up.</p>

Remark: Please do not soak gauge into water, oil or any solvent to avoid damage.

Due to our continuous improvement, all specifications are subject to change without prior notice.