



Quick Attachment Change



• One-wrench on tool body allows instant grab to change attachments.



• Low-noise Muffler Design



0.35 HP 0.50 HP 0.70 HP
71311 71211 71111
Low-noise Die Grinder

• Spindle Lock Design for simple one-wrench attachment changes

• Spindle Lock



71211-3
3" Extension Die Grinder



0.35 HP 0.50 HP 0.70 HP
74311 74211 74111
Low-noise Angle Die Grinder



54022
2" Angle Sander



54023
2" Angle Sander

Rear Exhaust / Air Inlet : 1/4" / Working Pressure : 6.2 Bar (90 PSI)

Item No.	Speed RPM	Collet mm/inch	Power KW/HP	Length mm/inch	Weight kg/lb	Air Consumption LPM / CFM	Vibration m/s²	Noise Level LpA / LwA
71311	25,000	6 (1/4)	0.26 (0.35)	185 (7.3)	0.5 (1.2)	57 (2.0)	3.40	76.0 / 87.0 DB
71211	22,000	6 (1/4)	0.37 (0.50)	204 (8.0)	0.7 (1.6)	93 (3.3)	< 2.5	79.9 / 90.9 DB
71111	20,000	6 (1/4)	0.52 (0.70)	214 (8.4)	0.8 (1.8)	102 (3.6)	< 2.5	80.9 / 91.9 DB
71211-3	20,000	6 (1/4)	0.37 (0.50)	236 (9.3)	0.9 (2.0)	93 (3.3)	< 2.5	81.3 / 92.3 DB
74311	20,000	6 (1/4)	0.26 (0.35)	169 (6.7)	0.6 (1.3)	68 (2.4)	3.48	74.2 / 85.2 DB
74211	19,000	6 (1/4)	0.37 (0.50)	182 (7.2)	0.9 (2.0)	93 (3.3)	6.04	78.8 / 89.8 DB
74111	18,000	6 (1/4)	0.52 (0.70)	192 (7.6)	1.0 (2.1)	102 (3.6)	< 2.5	80.3 / 91.3 DB
54022	20,000	-	0.26 (0.35)	169 (6.7)	0.6 (1.3)	68 (2.4)	< 2.5	77.6 / 88.6 DB
54023	20,000	-	0.26 (0.35)	169 (6.7)	0.6 (1.3)	68 (2.4)	5.28	77.6 / 88.6 DB