


# Cordless Torque Control Nutrunner

- Suitable for **Assembly Lines**
- Excellent repeatability of Clutch : high sensitive and fast shut-off
- **Simultaneous warning** by LED red light, buzzer and vibration can ensure the correct work procedures.
- The **Brushless Motor** is energy-saving and low maintenance.
- Compliance with ISO5393 (CmK >= 1.67 at +/- 10%)
- For management purposes, the data of motor running time and screwing numbers can be read by the external encoder.

• Torque Setting




• LED light




• LED lights indicate run, error, low battery and reverse.



• Electronic reverse switch on the left and right sides



• Non-contact trigger : soft start and easy control



**Lightweight and Compact !**



**18V 1/4" Cordless Torque Screwdriver**

**E-SD18LIK201** (1 ~ 6 Nm)

**E-SD18LIK202** (1.5 ~ 9 Nm)

**E-SD18LIK203** (2 ~ 12 Nm)





**E-AW18LIK-301** (4 ~ 15 Nm)

**18V 3/8" Cordless Torque Angle Wrench**

**E-AW18LIK-302** (8 ~ 25 Nm)

**E-AW18LIK-303** (15 ~ 35 Nm)

| Item No.      | Battery Voltage | Battery Capacity | Battery Type | No-Load Speed (RPM) | Drive (inch) | Capacity | Torque Range (Nm) | Torque Range (ft-lb) | Weight (kg / lb) | Charge Time | Contents                                             |
|---------------|-----------------|------------------|--------------|---------------------|--------------|----------|-------------------|----------------------|------------------|-------------|------------------------------------------------------|
| E-SD18LIK-201 | 18 V d.c.       | 2.5 AH           | Sliding      | 900                 | 1/4 Hex      | M3 ~ M5  | 1 ~ 6             | 0.7 ~ 4.4            | 1.3 / 2.9        | 60 min.     | 1 x Cordless Tool<br>1 x Battery Pack<br>1 x Charger |
| E-SD18LIK-202 |                 |                  |              | 700                 |              |          | 1.5 ~ 9           | 1.1 ~ 6.6            |                  |             |                                                      |
| E-SD18LIK-203 |                 |                  |              | 550                 |              | M4 ~ M6  | 2 ~ 12            | 1.5 ~ 8.9            | 1.7 / 3.6        |             |                                                      |
| E-AW18LIK-301 |                 |                  |              | 450                 | 3/8 SQ       |          | 4 ~ 15            | 3 ~ 11.1             |                  |             |                                                      |
| E-AW18LIK-302 |                 |                  |              | 260                 |              | M6 ~ M8  | 8 ~ 25            | 5.9 ~ 18.5           | 2.2 / 4.8        |             |                                                      |
| E-AW18LIK-303 |                 |                  |              | 200                 |              |          | 15 ~ 35           | 11.1 ~ 25.8          |                  |             |                                                      |