



Oil Pulse Wrench


• **Twin Drive Roller Blades** for improving the efficiency of impulse



- 25001T** **25003**
- 25002T** **25102**
- 25101T** **25202**

360° Air Exhaust

• **Double Chamber air motor design**



- 25201T** **25203**
- 25302**

360° Air Exhaust



- 25001ST** **25003S**
- 25002ST** **25102S**
- 25101ST** **25202S**
- 25202ST**

Item No.	Speed RPM	Drive inch	Bolt Capacity mm	Torque Range Nm/ft-lb	Shut-off Type	Weight kg/lb	Air Inlet inch	Working Pressure Bar / PSI
								P
25001T	4,500	3/8	M4 ~ M6	5 ~ 12 (3.7 ~ 8.9)	Auto	1.06 (2.3)	1/4	6.2 (90)
25002T	5,800	3/8	M6 ~ M8	10 ~ 23 (7.4 ~ 17)	Auto	1.06 (2.3)	1/4	6.2 (90)
25101T	5,800	3/8	M6 ~ M8	11 ~ 25 (8.1 ~ 18.4)	Auto	1.08 (2.4)	1/4	6.2 (90)
25201T	5,500	3/8	M8 ~ M10	20 ~ 42 (14.8 ~ 31)	Auto	1.30 (2.9)	1/4	6.2 (90)
25003	5,600	3/8	M6 ~ M8	9 ~ 17 (6.6 ~ 12.5)	Non	0.95 (2.1)	1/4	6.2 (90)
25102	5,800	3/8	M6 ~ M8	15 ~ 25 (11.1 ~ 18.4)	Non	0.95 (2.1)	1/4	6.2 (90)
25202	5,800	3/8	M8 ~ M10	20 ~ 34 (14.8 ~ 25.1)	Non	0.94 (2.1)	1/4	6.2 (90)
25203	5,500	3/8	M8 ~ M10	28 ~ 48 (20.7 ~ 35.4)	Non	1.35 (3.0)	1/4	6.2 (90)
25302	5,500	1/2	M10 ~ M12	35 ~ 57 (25.8 ~ 42)	Non	1.35 (3.0)	1/4	6.2 (90)
25001ST	4,500	3/8	M4 ~ M6	5 ~ 12 (3.7 ~ 8.9)	Auto	0.87 (1.9)	1/4	6.2 (90)
25002ST	6,000	3/8	M6 ~ M8	10 ~ 23 (7.4 ~ 17)	Auto	0.85 (1.9)	1/4	6.2 (90)
25101ST	6,000	3/8	M6 ~ M8	11 ~ 25 (8.1 ~ 18.4)	Auto	0.88 (1.9)	1/4	6.2 (90)
25202ST	6,000	3/8	M8 ~ M10	20 ~ 42 (14.8 ~ 31)	Auto	1.29 (2.8)	1/4	6.2 (90)
25003S	5,600	3/8	M6 ~ M8	9 ~ 17 (6.6 ~ 12.5)	Non	0.87 (1.9)	1/4	6.2 (90)
25102S	6,000	3/8	M6 ~ M8	15 ~ 25 (11.1 ~ 18.4)	Non	0.85 (1.9)	1/4	6.2 (90)
25202S	6,000	3/8	M8 ~ M10	20 ~ 34 (14.8 ~ 25.1)	Non	0.88 (1.9)	1/4	6.2 (90)

Oil Pulse Screwdriver



- 65001T** **65001**
- 65002T** **65102**
- 65101T** **65103**

 **360° Air Exhaust**








- 65201T** **65202**

 **360° Air Exhaust**



- 65001ST** **65003S**
- 65002ST** **65102S**
- 65101ST** **65103S**

Item No.	Speed RPM 	Drive inch 	Bolt Capacity mm	Torque Range Nm/ft-lb 	Shut-off Type	Weight kg/lb 	Air Inlet inch 	Working Pressure Bar / PSI P
65001T	4,500	1/4 Hex	M4 ~ M6	4 ~ 11 (3 ~ 8.1)	Auto	1.06 (2.3)	1/4	6.2 (90)
65002T	5,800	1/4 Hex	M5 ~ M8	7 ~ 19 (5.2 ~ 14)	Auto	1.06 (2.3)	1/4	6.2 (90)
65101T	5,800	1/4 Hex	M6 ~ M8	11 ~ 25 (8.1 ~ 18.4)	Auto	1.08 (2.4)	1/4	6.2 (90)
65201T	5,500	1/4 Hex	M8 ~ M10	20 ~ 35 (14.8 ~ 25.8)	Auto	1.30 (2.9)	1/4	6.2 (90)
65001	5,600	1/4 Hex	M5 ~ M8	7 ~ 14 (5.2 ~ 10.3)	Non	0.95 (2.1)	1/4	6.2 (90)
65102	6,000	1/4 Hex	M6 ~ M8	13 ~ 21 (9.6 ~ 15.5)	Non	0.95 (2.1)	1/4	6.2 (90)
65103	6,000	1/4 Hex	M6 ~ M8	17 ~ 30 (12.5 ~ 22.1)	Non	0.94 (2.1)	1/4	6.2 (90)
65202	5,500	1/4 Hex	M8 ~ M10	25 ~ 42 (18.4 ~ 31)	Non	1.35 (3.0)	1/4	6.2 (90)
65001ST	4,500	1/4 Hex	M4 ~ M6	4 ~ 11 (3 ~ 8.1)	Auto	0.87 (1.9)	1/4	6.2 (90)
65002ST	6,000	1/4 Hex	M5 ~ M8	7 ~ 19 (5.2 ~ 14)	Auto	0.85 (1.9)	1/4	6.2 (90)
65101ST	6,000	1/4 Hex	M6 ~ M8	11 ~ 25 (8.1 ~ 18.4)	Auto	0.88 (1.9)	1/4	6.2 (90)
65003S	5,600	1/4 Hex	M5 ~ M8	7 ~ 14 (5.2 ~ 10.3)	Non	0.87 (1.9)	1/4	6.2 (90)
65102S	6,000	1/4 Hex	M6 ~ M8	13 ~ 21 (9.6 ~ 15.5)	Non	0.85 (1.9)	1/4	6.2 (90)
65103S	6,000	1/4 Hex	M6 ~ M8	17 ~ 30 (12.5 ~ 22.1)	Non	0.88 (1.9)	1/4	6.2 (90)