



Oil Pulse Wrench




- **Twin Drive Roller Blades**
for improving the efficiency
of impulse



25001T **25003**
25002T **25102**
25101T **25202**

360° Air Exhaust



- **Double Chamber**
air motor design



25201T **25203**
25302

360° Air Exhaust



25001ST **25003S**
25002ST **25102S**
25101ST **25202S**
25202ST

Item No.	Speed RPM	Drive inch	Bolt Capacity mm	Torque Range Nm/ft-lb	Shut-off Type	Weight kg/lb	Air Inlet inch	Working Pressure Bar / PSI
25001T	4,500	3/8	M4 ~ M6	5 ~ 12 (3.7 ~ 8.9)	Auto	1.06 (2.3)	1/4	6.2 (90)
25002T	5,800	3/8	M6 ~ M8	10 ~ 23 (7.4 ~ 17)	Auto	1.06 (2.3)	1/4	6.2 (90)
25101T	5,800	3/8	M6 ~ M8	11 ~ 25 (8.1 ~ 18.4)	Auto	1.08 (2.4)	1/4	6.2 (90)
25201T	5,500	3/8	M8 ~ M10	25 ~ 42 (18.4 ~ 31)	Auto	1.30 (2.9)	1/4	6.2 (90)
25003	4,500	3/8	M6 ~ M8	25 ~ 42 (18.4 ~ 31)	Non	0.95 (2.1)	1/4	6.2 (90)
25102	5,800	3/8	M6 ~ M8	15 ~ 25 (11.1 ~ 18.4)	Non	0.95 (2.1)	1/4	6.2 (90)
25202	5,800	3/8	M8 ~ M10	20 ~ 34 (14.8 ~ 25.1)	Non	0.94 (2.1)	1/4	6.2 (90)
25203	5,500	3/8	M8 ~ M10	28 ~ 48 (20.7 ~ 35.4)	Non	1.35 (3.0)	1/4	6.2 (90)
25302	5,500	1/2	M10 ~ M12	25 ~ 52 (18.4 ~ 38.4)	Non	1.35 (3.0)	1/4	6.2 (90)
25001ST	4,500	3/8	M4 ~ M6	5 ~ 12 (3.7 ~ 8.9)	Auto	0.87 (1.9)	1/4	6.2 (90)
25002ST	6,000	3/8	M6 ~ M8	10 ~ 23 (7.4 ~ 17)	Auto	0.85 (1.9)	1/4	6.2 (90)
25101ST	6,000	3/8	M6 ~ M8	11 ~ 25 (8.1 ~ 18.4)	Auto	0.88 (1.9)	1/4	6.2 (90)
25202ST	6,000	3/8	M8 ~ M10	20 ~ 42 (14.8 ~ 31)	Auto	1.29 (2.8)	1/4	6.2 (90)
25003S	4,500	3/8	M6 ~ M8	9 ~ 17 (6.6 ~ 12.5)	Non	0.87 (1.9)	1/4	6.2 (90)
25102S	6,000	3/8	M6 ~ M8	15 ~ 25 (11.1 ~ 18.4)	Non	0.85 (1.9)	1/4	6.2 (90)
25202S	6,000	3/8	M8 ~ M10	20 ~ 34 (14.8 ~ 25.1)	Non	0.88 (1.9)	1/4	6.2 (90)



Oil Pulse Screwdriver



- **Twin Drive Roller Blades**
for improving the efficiency
of impulse




65001T **65001**

65002T **65102**

65101T **65103**

360° Air Exhaust



- **Double Chamber**
air motor design



65201T **65202**

360° Air Exhaust



65001ST **65003S**

65002ST **65102S**

65101ST **65103S**

Item No.	Speed RPM 	Drive inch 	Bolt Capacity mm	Torque Range Nm/ft-lb 	Shut-off Type	Weight kg/lb 	Air Inlet inch 	Working Pressure Bar / PSI 
65001T	4,500	1/4 Hex	M4 ~ M6	4 ~ 11 (3.0 ~ 8.1)	Auto	1.06 (2.3)	1/4	6.2 (90)
65002T	5,800	1/4 Hex	M5 ~ M8	7 ~ 19 (5.2 ~ 14.0)	Auto	1.06 (2.3)	1/4	6.2 (90)
65101T	5,800	1/4 Hex	M6 ~ M8	11 ~ 25 (8.1 ~ 18.4)	Auto	1.08 (2.4)	1/4	6.2 (90)
65201T	5,500	1/4 Hex	M8 ~ M10	20 ~ 35 (14.8 ~ 25.8)	Auto	1.30 (2.9)	1/4	6.2 (90)
65001	4,500	1/4 Hex	M5 ~ M8	7 ~ 14 (5.2 ~ 10.3)	Non	0.95 (2.1)	1/4	6.2 (90)
65102	5,800	1/4 Hex	M6 ~ M8	13 ~ 21 (9.6 ~ 15.5)	Non	0.95 (2.1)	1/4	6.2 (90)
65103	5,800	1/4 Hex	M6 ~ M8	17 ~ 30 (12.5 ~ 22.1)	Non	0.94 (2.1)	1/4	6.2 (90)
65202	5,500	1/4 Hex	M8 ~ M10	25 ~ 42 (18.4 ~ 31)	Non	1.35 (3.0)	1/4	6.2 (90)
65001ST	4,500	1/4 Hex	M4 ~ M6	4 ~ 11 (3.0 ~ 8.1)	Auto	0.87 (1.9)	1/4	6.2 (90)
65002ST	6,000	1/4 Hex	M5 ~ M8	7 ~ 19 (5.2 ~ 14.0)	Auto	0.85 (1.9)	1/4	6.2 (90)
65101ST	6,000	1/4 Hex	M6 ~ M8	11 ~ 25 (8.1 ~ 18.4)	Auto	0.88 (1.9)	1/4	6.2 (90)
65003S	4,500	1/4 Hex	M5 ~ M8	7 ~ 14 (5.2 ~ 10.3)	Non	0.87 (1.9)	1/4	6.2 (90)
65102S	6,000	1/4 Hex	M6 ~ M8	13 ~ 21 (9.6 ~ 15.5)	Non	0.85 (1.9)	1/4	6.2 (90)
65103S	6,000	1/4 Hex	M6 ~ M8	17 ~ 30 (12.5 ~ 22.1)	Non	0.88 (1.9)	1/4	6.2 (90)